

INSTALLATION INSTRUCTIONS

2013-2018 Tracker Convertible Top Targa V 18 WT / Combo

PARTS LIST Top / Boot / Frame / Hardware / Full Frame (2 pc) Top with Front Curtain Boot Hardware Kit WEB STRAP IS ONLY USED WHEN FRONT **CURTAIN IS NOT INSTALLED** EYE STRAP CONSOLE **CARPETED LEDGE VERSA TRACK** 2"

INSTALLATION

STEP 1

Install eye straps on top of gunnel, 2" behind console and 2" from inside edge of gunnel. Install hardware into inside Versa Track. Do not tighten. Slide to proper location and tighten.

STEP 2

Wrap the web strap around the frame through the cut-out in the front canvas and attach hook to eye strap. Adjust strap for a tight and smooth appearance.

STEP 3

Stow in radar arch position by releasing the web straps from the eye straps and fold frame toward the back of the boat. Install the boot. Top may be left in radar arch position.

STEP 4

Top may also be stored by laying across the rear of the boat. Loosen the fasteners and slide the hold-down arms toward the rear of the boat.

STEP 5

Return the top to the raised position. Check that the support arms and straps on the bimini are in the proper place and secure. The top should be free of wrinkles.



CARE



WARNING

DO NOT TRAILER BOAT WITH TOP IN RADAR ARCH POSITION!





SNAPS FOR THE SIDE CURTAINS INSTALL UNDERNEATH THE GUNNEL.